

## A2 Industrial Cable Gland



<b>Size :</b>	1 16mm to 1 15mm & ½" to 3½"
<b>Standard :</b>	BS 6121 :Part-1 : 2005 ,EN 50262 :1999
<b>Function :</b>	Providing seal on outer sheaths of all types of unarmoured cable in indoor and outdoor area.
<b>Ingress Protection:</b>	IP66
<b>Material:</b>	Brass BS 2874
<b>Thread:</b>	Metric,NPT and PG
<b>Operating Temp:</b>	-60°C to +150°C
<b>Features:</b>	Outer Displacement seal
<b>Accessories:</b>	Shroud,Earth Tag,Lock Nut,Thread Seal,Adaptor & Reducer
<b>Packing:</b>	Gland Kit for 16mm to 32 mm contain 2 Brass Cable Gland,Two Galvanized Steel Lock Nut,2 Brass Earth Tag and Two PVC Shroud,For sizes 40 mm and above each kit contains one of each component.

**Table**

Size	Thread "C"		Thread Length "D"	Cable Dia. "B"		Across Flat	Across Corners	CAT NO.
	Metric	NPT		Min."A"	Max."B"			
16	16	-	15.00	3.10	12.00	20.00	23.00	MCA2I-16
20S	20	½"	15.00	6.10	16.20	24.00	26.50	MCA2I-20S
20	20	½"	15.00	6.50	20.25	27.00	30.00	MCA2I-20
25	25	¾"	15.00	11.10	26.00	36.00	39.75	MCA2I-25
32	32	1"	15.00	17.00	33.70	41.00	46.00	MCA2I-32
40	40	1¼"	15.00	22.00	40.10	49.25	55.00	MCA2I-40
50S	50	1½"	15.00	29.80	45.75	54.75	61.30	MCA2I-50S
50	50	2"	15.00	36.90	53.10	60.00	66.50	MCA2I-50
63S	63	2"	15.00	42.20	59.40	70.25	77.50	MCA2I-63S

63	63	2½"	15.00	48.30	65.00	74.75	83.00	MCA2I-63
75S	75	2½"	15.00	54.20	71.40	80.00	89.00	MCA2I-75S
75	75	3"	15.00	59.80	78.00	84.00	94.00	MCA2I-75
90	90	3"	18.00	66.60	89.25	107.00	119.70	MCA2I-90
100	100	3½"	20.00	77.00	102.00	122.00	132.00	MCA2I-100
110	110	-	20.00	86.00	110.50	138.00	148.00	MCA2I-110
115	115	-	20.00	86.00	110.50	138.00	148.00	MCA2I-115