

Nylon IP 68 Cable Glands



Size :	PG 7 to PG 48 and M 12 to M63
Application :	Suitable for indoor and outdoor conditions for inarmoured cable. Mostly used in motors, junction boxes, machinery, equipment, etc.
Ingress Protection:	IP66
Thread :	Metric.PG
Material :	Nylon Polyamide
Accessories:	Lock Nut

PG Thread Gland Selection Chart

Gland Size	Thread "C"	Cable Range Dia.		CAT NO.
		Min. "A"	Max. "B"	
7	PG-7	3	6.5	CNCG-7
9	PG-9	4	8	CNCG-9
11	PG-11	5	10	CNCG-11
13.5	PG-13.5	6	12	CNCG-13
16	PG-16	10	14	CNCG-16
21	PG-21	13	18	CNCG-21
25	PG-25	16	21	CNCG-25
26	PG-26	18	25	CNCG-26
36	PG-36	22	32	CNCG-35
42	PG-42	28	38	CNCG-42
48	PG-48	35	45	CNCG-48

Metric Thread Gland Selection Chart

Gland Size	Thread "C"	Cable Range Dia.	CAT NO.
------------	------------	------------------	---------

Min. "A"	Max. "B"			
12	M 12	3	6	CNCG-12
16	M 16	5	10	CNCG-16
20	M 20	8	13	CNCG-20
25	M 25	10	17	CNCG-25
35	M 35	15	21	CNCG-35
40	M 40	19	28	CNCG-40
50	M 50	25	35	CNCG-50
63	M 63	35	45	CNCG-63

Diamenesion Are in mm