

## TRS Cable Gland



<b>Size :</b>	16mm to 50mm
<b>Standard :</b>	BS 6121: Part -1 :2005,EN 50262:1999
<b>Function :</b>	Recommended for use with braided, co-axial or SWA cables. A rubber seal compresses on cable to provide a tight fit against cable.
<b>Ingress:</b>	IP66
<b>Material:</b>	Brass BS 2874
<b>Thread:</b>	Metric
<b>Accessories:</b>	Shroud, Earth Tag, Lock Nut and Serrated Washer
<b>Features:</b>	Outer Displacement Seal
<b>Packing:</b>	Gland Kit for 16mm to 32 mm Contain 2 Brass Cable Gland, 2 Galvanized Steel Lock Nut, 2 Brass Earth Tag and 2 PVC Shroud. For sizes 40 mm and above each kit includes one off each component.

Table

Gland Size	Entry Thread "C" Metric	Length "D"	Cable Dia. "A" Max	Cable Dia. "B" Max.	Across Flat	Across Corners	CAT NO.
16	16	8	3.00	7.00	20.00	23.00	MCTRS-16
20S	20	10	7.00	10.00	24.00	27.00	MCTRS-20S
20	20	10	10.00	14.50	27.70	31.00	MCTRS-20
25	25	10	14.50	20.50	35.00	39.00	MCTRS-25
32	32	10	20.50	26.50	43.00	47.50	MCTRS-32
40	40	15	26.50	34.50	51.50	57.00	MCTRS-40
50	50	15	34.50	43.50	58.50	65.00	MCTRS-50

Dimensions are in mm